

MODEL

# G130



Maximum filter life will be achieved with this product when one welder is welding up to 10 pounds of weld wire per week



**Capacity:** 150 CFM Max, 110 in.W.G. Max

**Motor:** 2.3 HP (1700 Watts), Direct Drive, 1500+ hr. Duty

**Voltage:** Single phase, 110V, 60Hz

**Full Load Amps:** 15.1

**Blower:** Single Stage Tapered 8.4" dia. Tangential Discharge Blower

**Sound Level:** 75 dBA

**Silencing:** Integral Acoustical Plenum with Low Frequency Dampening

**Controls:** Manual on/off switch, Minihelic Filter Condition Gauge

**Cabinet Dimensions (HxLxD):** 18" x 16" x 14"

**Weight:** 50 lbs.

**Filter Cartridge:** (1) PL-10D12-A15

**Filter Media Area:** 67 sq.ft.

**Filter Type:** Nanofiber MERV15

**Dust Containment:** Vacuum / sweep out filter plenum

**Spark Arrestance:** (1) Metal Mesh Screen MM-12121

**Configuration:** (1) 2" Flex Hose, 15'

**Filter Cleaning:** Ball-Valve Activated Pulse Cleaning, 1/4" NPT Compressed Air Connection

**Options:**

- Intake Attachment Options:
  - Flared Cone 7" H x 10" W — FC-VB (**included**)
  - Slotted Hood 15" L — ST-VB
  - 2" Pipe with magnetic base — GNT-VB
- CSA Certification — CSA-100
- UL Certification — Contact Customer Service

**Warranty:**

Visit [ventboss.com/terms](http://ventboss.com/terms) for full warranty details.

